

BALLOON	PIPE
#1	¼" O.D. BLUE
* 2	¾" O.D. BLUE
#3	½" O.D. BLUE
#4	¾" O.D. YELLOW
* 5	1∕4" O.D. BLACK
#6	¾" O.D. BLACK
# 7	HOSE ASSY #8

KNEELING SYSTEM = UP (CTR'L + UP ENERGIZED) DOWN (CTR'L + DOWN ENERGIZED)

CONTROL VALVE OPT. "LOW-BUOY", "A" OR "B" SETTING:

POSITION "A": VALVE IS OPEN,

AIR FLOW BETWEEN SUPPLY (S) AND DELIVERY (D), LOW-BUOY IS IN FUNCTION.

POSITION "B":

VALVE CLOSED, AIR DOES'NT FLOW BETWEEN SUPPLY (S) AND DELIVERY (D), LOW-BUOY IS NOT IN FUNCTION.

TUBE COLOR CODING		
LINE TYPE	COLOR	CIRCUIT
	BLUE	SUSPENSION
	BLACK	ACCESSORIES
	YELLOW	DARKING BRAKES

PREVOST

DESCRIPTION:

X3-45 COACH, WITH INDEPENDENT FRONT SUSPENSION (I.F.S.) WITH OPTION FRONT KNEELING, LOW-BUOY & HIGH-BUOY COMBINATION

REV.:

PAGE:

D140383 P6.1

DATE: 2011/10