

BALLOON	PIPE
#1	¼" O.D. BLUE
#2	¾'' O.D. BLUE
#3	½" O.D. BLUE
# 4	⅓'' O.D. YELLOW
#5	3∕8" O.D. BLACK
*6	¾'' O.D. BLACK

NOTE:

KNEELING SYSTEM = UP (CTR'L + UP ENERGIZED)

DOWN (CTR'L + DOWN ENERGIZED)

TUBE COLOR CODING		
LINE TYPE	COLOR	CIRCUIT
	BLUE	SUSPENSION
— — — — .	BLACK	ACCESSORIES
	YELLOW	PARKING BRAKES

CONTROL VALVE OPT. "LOW-BUOY" , "A" OR "B" SETTING:

POSITION "A":

VALVE IS OPEN, AIR FLOW BETWEEN SUPPLY (S) AND DELIVERY (D), LOW-BUOY IS IN FUNCTION.

POSITION "B":

VALVE CLOSED, AIR DOES'NT FLOW BETWEEN SUPPLY (S) AND DELIVERY (D), LOW-BUOY IS NOT IN FUNCTION.

PREVOST®

X3-45 COACH, WITH FRONT BEAM AXLE WITH OPTION FRONT KNEELING, LOW-BUOY & HIGH-BUOY COMBINATION

EFF. W/VEH :

#8-9430

DATE: 2008/04 REV.: PAGE:

D140331 P4.1