



NOTE:

CONTROL VALVE OPT. "LOW-BUOY" , "A" OR "B" SETTING:

POSITION "A": VALVE IS OPEN,  
AIR FLOW BETWEEN SUPPLY (S) AND  
DELIVERY (D) , LOW-BUOY IS NOT IN FUNCTION.

POSITION "B": VALVE CLOSED,  
AIR DOESN'T FLOW BETWEEN SUPPLY (S) AND  
DELIVERY (D) , LOW-BUOY IS IN FUNCTION.

TUBE COLOR CODING	
ACTIVE COLOR	CIRCUIT
→ → RED	SECONDARY
→ → GREEN	PRIMARY & SUPPLY
→ → YELLOW	PARKING BRAKE
→ → BLUE	SUSPENSION
→ → BLACK	ACCESSORIES

BALLOON	PIPE
*1	1/4" O.D. BLACK
—	STD PIPING
—	OPTIONAL PIPING

H3-41 & H3-45 COACHES,  
ENGINE 2002 WITH  
FRONT BEAM AXLE

WITH OPTION FRONT KNEELING,  
REAR LOW-BUOY & SPEED  
SWITCH (5 MPH) COMBINATION.  
(NOTE: THIS DRAWING MUST BE READ  
IN CONJUNCTION WITH D140297 P2)

D140297 P3 REV. A

DATE : 2003/02