



NOTE:
 CONTROL VALVE OPT. "LOW-BUOY", "A" OR "B" SETTING:
 POSITION "A": VALVE IS OPEN,
 AIR FLOW BETWEEN SUPPLY (S) AND
 DELIVERY (D), LOW-BUOY IS IN FUNCTION.
 POSITION "B": VALVE CLOSED,
 AIR DOES'NT FLOW BETWEEN SUPPLY (S) AND
 DELIVERY (D), LOW-BUOY IS NOT IN FUNCTION.



LOW-BUOY ONLY



HIGH-BUOY ONLY

TUBE COLOR CODING		
LINE TYPE	COLOR	CIRCUIT
---	BLUE	SUSPENSION

B	2015/02	O.C. #2013172	Rob.
A	2013/05	O.C. #2011158	Rob.
REV	DATE	DESCRIPTION	BY

PREVOST®
 Prevost Car Inc. Ste-Catherine, Quebec, Canada G0R 2V0
 Rob. DATE: 2013/05 APPR: M.J.H.
 GENERAL TOL. mm ± N/A deg ± N/A ECHELLE: N/A POISS: D140383
 REF. DRAWING: D140384

MATERIAL:	INSTALLATION
FINISH:	N/A
REF.:	X3-45 WITH KNEELING OPTION
TITLE:	LOW-BUOY & HIGH-BUOY OPTIONS
PART NUMBER:	D140405 P4 CAD

NUMEROTATION RANGE:	400 @ 499	LEGEND:	"RES-1": SERVICE TANK	"PT.": PILOT
LAST NUMBER USED:	416	"SER-": SERVICE	"P-": PRESSURE	"A-": DRAIN
UNUSED NUMBERS:	401,402,411,412,413	"EM-": EMERGENCY	"A-": ACCESSORY	"ES-": SOLENOID
		"EXH-": EXHAUST	"D-": DELIVERY	"SP-": SPRING
		"BAL-": BALANCE	"S-": SUPPLY	

THIS DOCUMENT IS THE EXCLUSIVE PROPERTY OF PREVOST CAR INC. STE-CATHERINE, QUE., AND MAY NOT BE USED, OR REPRODUCED, NOR ITS CONTENT OR PART THERE OF DISCLOSED TO OTHERS BY ANY PERSON OR COMPANY SAVE WITH THE EXPRESS CONSENT IN WRITING FROM PREVOST CAR INC.