



KNEELING SYSTEM = UP (CTR'L + UP ENERGIZED)
 DOWN (CTR'L + DOWN ENERGIZED)

BALLOON	PIPE
*1	1/4" O.D. BLUE
*2	3/8" O.D. BLUE
*3	1/2" O.D. BLUE
*4	3/8" O.D. YELLOW
*5	3/8" O.D. BLACK
*6	3/4" O.D. BLACK

TUBE COLOR CODING		
LINE TYPE	COLOR	CIRCUIT
---	BLUE	SUSPENSION
---	BLACK	ACCESSORIES
---	YELLOW	PARKING BRAKES

NOTE:
 CONTROL VALVE OPT. "LOW-BUOY" , "A" OR "B" SETTING:
POSITION "A": VALVE IS OPEN,
 AIR FLOW BETWEEN SUPPLY (S) AND
 DELIVERY (D) , LOW-BUOY IS IN FUNCTION.

POSITION "B": VALVE CLOSED,
 AIR DOES'NT FLOW BETWEEN SUPPLY (S) AND
 DELIVERY (D) , LOW-BUOY IS NOT IN FUNCTION.

PREVOST®

DESCRIPTION:
 X3-45 COACH, WITH FRONT BEAM AXLE
 WITH OPTION FRONT KNEELING & LOW-BUOY COMBINATION

EFF. W/VEH : TO FOLLOW
 DATE: 2006/03
 REV.: A

PAGE:
 D140331 P2.1