



KNEELING SYSTEM = UP (CTR'L + UP ENERGIZED)  
 DOWN (CTR'L + DOWN ENERGIZED)

BALLOON	PIPE
*1	1/4" O.D. BLUE
*2	3/8" O.D. BLUE
*3	1/2" O.D. BLUE
*4	3/8" O.D. YELLOW
*5	3/8" O.D. BLACK
*6	3/4" O.D. BLACK

TUBE COLOR CODING		
LINE TYPE	COLOR	CIRCUIT
---	BLUE	SUSPENSION
---	BLACK	ACCESSORIES
---	YELLOW	PARKING BRAKES

NOTE:

CONTROL VALVE OPT. "LOW-BUOY" , "A" OR "B" SETTING:

POSITION "A": VALVE IS OPEN,  
 AIR FLOW BETWEEN SUPPLY (S) AND  
 DELIVERY (D) , LOW-BUOY IS IN FUNCTION.

POSITION "B": VALVE CLOSED,  
 AIR DOES'NT FLOW BETWEEN SUPPLY (S) AND  
 DELIVERY (D) , LOW-BUOY IS NOT IN FUNCTION.

**PREVOST®**

X3-45 COACH, WITH FRONT BEAM AXLE  
 WITH OPTION FRONT KNEELING,  
 LOW-BUOY & HIGH-BUOY COMBINATION

EFF. W/VEH : TO FOLLOW

DATE: 2006/03 REV.: A

PAGE:

D140331 P4.1