



NOTE:

CONTROL VALVE OPT. "LOW-BUOY" , "A" OR "B" SETTING:

POSITION "A": VALVE IS OPEN,  
AIR FLOW BETWEEN SUPPLY (S) AND  
DELIVERY (D) ,LOW-BUOY IS NOT IN FUNCTION.

POSITION "B": VALVE CLOSED,  
AIR DOES'NT FLOW BETWEEN SUPPLY (S) AND  
DELIVERY (D) ,LOW-BUOY IS IN FUNCTION.

TUBE COLOR CODING		
ACTIVE	COLOR	CIRCUIT
->->	RED	SECONDARY
->->	GREEN	PRIMARY & SUPPLY
->->	YELLOW	PARKING BRAKE
->->	BLUE	SUSPENSION
->->	BLACK	ACCESSORIES

BALLOON	PIPE
#1	1/4" O.D. BLACK
—	STD PIPING
—	OPTIONAL PIPING

H3-41 & H3-45 COACHES,  
ENGINE 2002 WITH  
FRONT BEAM AXLE

WITH OPTION FRONT KNEELING,  
REAR LOW-BUOY & SPEED  
SWITCH ( 5 MPH ) COMBINATION.  
( NOTE: THIS DRAWING MUST BE READ  
IN CONJUNCTION WITH D140297 P2)

DATE : 2004/01

D140297 P3 REV. B