

**PREVOST**ENREGISTRÉ - REGISTERED  
**ISO 9001 & ISO 14001**

# MAINTENANCE INFORMATION

Mi99-11

DATE : January 1999

SECTION : 06

SUBJECT : RAMCO MIRROR WATERTIGHTNESS

**Important Notice :** This modification is recommended by Prévost Car to increase your vehicle's performance. Note that no reimbursement will be awarded for carrying out this modification.

## APPLICATION

| Model  | VIN  |  |  |
|--|--|--|--|
| M-40, M-45 and M-45E Bus Shells<br>Model Year: 1990-1999 | From 2P9M33402L1001685 up to 2PCE33497X1026827 incl. |  |  |
| XL-40 and XL-45 Coaches<br>Model Year: 1991-1999         | From 2P9L33401M1001707 up to 2PCL33494X1026825 incl. |  |  |
| H3-40 and H3-45 VIP Bus Shells<br>Model Year: 1994-1999  | From 2P9V33400R1001004 up to 2PCV33490X1012963 incl. |  |  |
| H3-41 and H3-45 Coaches<br>Model Year: 1993-1999         | From 2P9H3340XP1001375 up to 2PCH33492X1012962 incl. |  |  |

## DESCRIPTION

A connector sealing kit is available for electrically adjustable RAMCO mirrors.

- Order one kit #064904 for each set of two flat type mirrors to modify.

**OR**

Order one kit #064905 for each set of two combination flat and convex type mirrors to modify.

- Extractor tool #682257 is needed to carry out these modifications; order if necessary.

**Note:** Some vehicles included in the above application listing may already be fitted with watertight connector seals. Verify connections on your vehicle before ordering any material.

## MATERIAL

| Part No. | Description   | Qty |
|----------|---|-----|
| 064904   | Connector Sealing Kit for one set of two RAMCO Flat Type Electrically Adjustable Mirrors                        | 1   |
| 064905   | Connector Sealing Kit for one set of two RAMCO Combination Flat and Convex Type Electrically Adjustable Mirrors | 1   |
| 682257   | Extractor Tool  | 1   |

**Note :** Material can be obtained through regular channels.

## PROCEDURE

**Warning :** Park vehicle safely, apply parking brake, stop engine and set battery master switch(es) to the OFF position prior to working on the vehicle.

1. Remove a mirror as explained in the Maintenance Manual, section 18.
2. Observe if the connector is fitted with watertight seals.
  - If connector is not equipped with seals, order the appropriate sealing kit and carry out modifications as per instructions included in kit.
  - If connector is already equipped with seals, it is not necessary to order sealing kit.